110275-120 US1 PATENT

What is claimed is:

1. A wireless communications system for use in the transportation industry, comprising:

5 at least one data transmission device including a user interface providing a user functionality to enter into said at least one data transmission device at least one predefined data field and data associated with the at least predefined data field, 10 the at least one predefined data field and the data associated therewith formatted in accordance with a standard format including at least one first standard format for the at least one predefined data field and at least one second standard format for the data, and 15 the data including at least one of economic and logistical data relating to at least one of shipment, delivery and receipt of shipped goods;

at least one remote computing device,
operatively connectable to said at least one data

20 transmission device, and receiving each of the at
least one predefined data field and the data
transmitted by said at least one data transmission
device, and processing the at least one first
standard format for the at least one predefined data

25 field and the at least one second standard format for

10

15

20

25

110275-120 US1 PATENT

the data responsive to the standard format using at least one application program stored on said at least one remote computing device configured to receive the standard format comprising the at least one first standard format for the at least one predefined data field and the at least one second standard format for the data; and

at least one network operatively connectable to each of said at least one data transmission device and each of said at least one remote computing device, and transmitting the at least one first standard format for the at least one predefined data field and the at least one second standard format for the data responsive to the standard format to said at least one remote computing device and receiving the at least one first standard format for the at least one predefined data field and the at least one second standard format for the data responsive to the standard format format for the data responsive to the standard format from said at least one data transmission device.

2. The wireless communications system as recited in claim 1, wherein each standard format comprises a bill of lading, a weight, a shipper zip, a consignee zip, a number of pieces shipped, a

delivery date, a name of an individual who signed a delivery receipt, a product number, an indication that the goods are delivered, an indication that the goods are picked up, an estimated time of arrival, a comment, an indication that a trailer is being dropped off, an indication that a trailer is being picked up, a drop/hook indication, and an indication that the goods are at least one of over, short and damaged.

10

15

5

3. The wireless communications system as recited in claim 1, wherein each of the at least one predefined data field comprises a user-entered predefined representation corresponding to at least one of a word and phrase and facilitates utilization of at least a portion of the transmitted data with at least one of the data file and the data file format associated with at least application program residing on said at least one remote computing device.

20

25

4. The wireless communications system as recited in claim 3, wherein each of the at least one predefined data field comprises a user-entered predefined representation corresponding to at least one of a word and phrase comprising a bill of lading, a

weight, a shipper zip, a consignee zip, a number of
pieces shipped, a delivery date, a name of an
individual who signed a delivery receipt, a product
number, an indication that the goods are delivered,
an indication that the goods are picked up, an
estimated time of arrival, a comment, an indication
that a trailer is being dropped off, an indication
that a trailer is being picked up, a drop/hook
indication, and an indication that the goods are
over, short or damaged.

5. The wireless communications system as recited in claim 1, wherein each of the at least one data transmission device is a portable device.

15

20

- 6. The wireless communications system as recited in claim 1, wherein each of the at least one data transmission device verifies that the user has entered a valid predefined data field prior to transmission.
- 7. The wireless communications system as recited in claim 1, wherein each of the at least one remote computing device verifies that a valid data

110275-120 US1 PATENT

field has been received prior to utilizing the transmitted data.

- 8. The wireless communications system as recited in claim 1, wherein each of the at least one networks comprise:
 - a scheduler determining which of the at least one data transmission devices are active;
- a device action manager receiving notification

 from said scheduler and monitoring which of said at

 least one transmission devices have requested to

 download a message from the at least one remote

 computing device;
- a download manager receiving notification via said

 15 scheduler at which time messages associated with each
 of the at least one data transmission device are to be
 downloaded;
- a message lookup manager determining an identifier associated with each message associated with each of the at least one transmission device and selecting those messages that have not been downloaded from the at least one remote computing device to the respective first communications device; and
- a message processor for retrieving messages from
 the remote computing device and transmitting the

110275-120 US1 PATENT

messages to the respective data transmission device as determined by a selection system.

- 9. The system according to claim 8, wherein the at least one data transmission device is a wireless 5 messaging device having a first identifier associated with said at least one network and the at least one remote computing device is an e-mail server storing messages for at least one e-mail account, each e-mail account having a second identifier associated 10 therewith, wherein the at least one data transmission device and the at least one remote computing device transmit signals to each other via said networks, and wherein the predetermined criteria are respective identifiers associated with each of the at least one 15 data transmission device and the at least one remote computing device.
- 11. The system according to claim 9, wherein said 20 signals comprise at least one of an electronic mail message, an electronic page, and a paging message.
 - 12. The system according to claim 8 wherein said download manager downloads messages subsequent to receiving an indication from said scheduler and said

25

lookup manager.

- 13. The system according to claim 8 wherein said message processor converts the message format of the at least one second communications device to a message format of the at least one data transmission device.
 - 14. The system according to claim 8 wherein said lookup manager deletes a message record when a corresponding message is transmitted to the at least one data transmission device.
- 15. The system according to claim 8 wherein said scheduler further determines the time at which each of the at least one data transmission devices are to receive a message.
- 16. The system according to claim 1 wherein each of said at least one data transmission device have a common domain name associated therewith.
 - 17. The system according to claim 8, wherein said scheduler accesses subscriber information from the selection system to determine user specified download times.

- 18. A method for standardizing data communications, pertaining to economic and/or logistical data relating to the shipment, delivery and/or receipt of goods, between at least one data transmission device and at least one remote computing device, comprising the steps of:
- a) entering into at least one data transmission device a predefined data field and associated data, wherein the predefined data field and the associated data comprise a standard format;
 - b) transmitting the predefined data field and the associated data to at least one remote computing device;
- 15 c) receiving by the at least one remote computing device the predefined data field and associated data; and
- d) utilizing at least a portion of the data received in step c) with at least one of a data file 20 and a data format associated with at least one application program residing on the at least one remote computing device.
- 19. The method according to claim 18, wherein 25 each of the at least one predefined data field

10

comprises a user-entered pre-defined representation corresponding to a word or phrase pertaining to at least one of a bill of lading, a weight, a shipper zip, a consignee zip, a number of pieces shipped, a delivery date, a name of an individual who signed a delivery receipt, a product number, an indication that the goods are delivered, an indication that the goods are picked up, an estimated time of arrival, a comment, an indication that a trailer is being dropped off, an indication that a trailer is being picked up, a drop/hook indication, and an indication that the goods are over, short or damaged.

- 20. The method according to claim 18, wherein each of the at least one remote computing device verifies that a valid data field has been received prior to utilizing the transmitted data.
- 21. The method according to claim 18, wherein
 20 each of the at least one data transmission device is
 a portable device.
 - 22. The method according to claim 18, wherein each of the at least one data transmission device

110275-120 US1 PATENT

verifies that the user has entered a valid predefined data field prior to transmission.